

The machinery is used to fold flat linen:

- **NAPKINS**
- **PILLOWCASES**
- **BATH TOWELS**
- **SMALL TOWELS**



## MAXIMUM COMPACTNESS AND INDEPENDENCE

Via the keyboard on the operating panel, the operator must only press START, the machine recognizes automatically the format of the linen.

The machine automatically folds, stacks and counts the pieces folded and transports them over the conveyor to the storage area, where as much as 5 stacks can be held before an operator needs to unload the conveyor.

- **1300 PIECES/H**

**HIGH QUALITY -**

- **LOW PERCENTAGE OFF REFUSE**

**SILENT -**

## CHARACTERISTICS:

- ✓ High quality folding with all the types of material;
- ✓ Optimal folding with synthetic material;
- ✓ Speed of approximately 1300 pieces/hour;
- ✓ Maximum precision;
- ✓ Automatic detection of pieces;
- ✓ Nonexistence noise;
- ✓ Independent aspiration
- ✓ Simple to use;
- ✓ Low maintenance;
- ✓ Optimal relation between quality and price.

## TECHNICAL SPECIFICATIONS:

<b>GROSS WEIGHT</b>	Libbre 564.38 - 256 KG		
<b>DIMENSIONS</b>		inches	mm
<b>LENGHT</b>	SLOWLY BENDING	82.67	2100
	WAREHOUSE	47.24	1200
	*FEEDING BELT	33.46	*850
<b>WIDTH</b>	CONSTANT	23.22	590
<b>HEIGHT</b>	ADJUSTABLE	35.43- 45.27	900-1150

\* Optional

<b>TOTAL LENGHT MACHINERY STANDARD</b>	<b>129.92</b>	<b>3.300 mm</b>
<b>TOTAL LENGHT + FEEDING BELT*</b>	<b>163.38</b>	<b>4.150 mm</b>

<b>NOMINAL SUPPLY VOLTAGE</b>	380 volt, 3 phase+N+PE
<b>INSTALLED POWER</b>	5 Kwatt
<b>SUPPLY VOLTAGE - CONTROL PANEL</b>	24 volt AC
<b>PRESSURE MAXIMUM AIR FEEDING</b>	6 bar

## LINEN SIZES:

<b>WIDTH LINEN</b>	Maximum 590 mm	23.22
	Minimum 185 mm	7.28
<b>LENGHT LINEN</b>	Maximum 950 mm	37.40
	Minimum 185 mm	7.28

Only constructor: